

# Technical Data Information

## ***ELCO Block - it***

Water Based, Rapid Dry, Stain Block Primer / Undercoat

**THE PRODUCT:** Rapid drying Acrylic Coating with excellent binding power & stain block properties.  
For interior or exterior surfaces.

1 component pure acrylic paint, fast drying time

### **PROPERTIES**

- Excellent adhesion on broad variety of substrates
- environmentally friendly
- resists yellowing
- low odour
- low VOC

### **TECHNICAL DATA**

Product: White  
gloss level: Matt  
specific gravity: 1.1 -1.3  
solids 54% weight  
dust free: 30 minutes  
fully cured: 7 days\*

*\*depending upon relative humidity, air circulation, temperature and film thickness*

### **APPLICATION**

#### ***Surface preparation***

Remove any dust oil or contaminants which may inhibit optimum adhesion.

#### ***Application***

By brush roller or spray

Do not apply at ambient or surface temperatures below 12°C or above 85% relative humidity.  
Ensure adequate ventilation.

#### ***Cleaning***

Wash up in water immediately after use.  
Dried paint can be removed with general thinners.

### **TECHNICAL HELP LINE.**

If you require any further information or have any questions please call us on tollfree 1800 675 650 and one of our experienced staff will be more than happy to assist.

The statements above are compiled from our field of production and according to the latest technological developments and application techniques. Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet. ELCO International Pty Ltd and associated group of companies shall not be responsible for any damage or injury resulting from abnormal use of the material, from any failure to adhere or observe the recommendations, or from any hazards inherent in the nature of the material. It is the users responsibility to evaluate the information contained herein and use this product safely and within the current laws and regulations.