

ELCO Protekt-it PLUS-

Clear Water Based Protective Coating for use on RAW MASONRY and Painted Surfaces

SACRIFICIAL ANTI-GRAFFITI COATING SYSTEM

Can be removed with hot water & low pressure. Chemicals are not required

THE PRODUCT

ELCO Protekt-it PLUS is a single component water based coating system. This coating acts as a sacrificial barrier against all forms of graffiti, pollutants, moisture and even the penetration of felt pens, crayons and spray paints. It can be applied onto painted and unpainted surfaces including concrete, stone, timber, brick, concrete blocks, sandstone, limestone, Hebel blockwork, artworks, murals etc. Easy to apply.

Graffiti is easily removed using hot water without damage to the substrate.

PROPERTIES

- long term protection
- environmentally friendly
- applied to painted surfaces without harm
- applies as a milky solution and dries to a clear barely noticeable film
- removal process - hot water
- reduced absorption of water and pollution
- rapid drying time
- low odour
- stringent quality control procedures
- Australian owned and made

TECHNICAL DATA

Product: milky aqueous solution
specific gravity: 1.0
solids: 16% weight
dust free: 15 - 30 minutes*
odour: slight
coverage: 8 – 10 m² per coat

*depending upon relative humidity, air circulation, temperature and film thickness

SURFACE PREPARATION

Surface must be clean and sound, free from oils, surfactants, dust, chalk, mildew and any other contaminants. If any of these are present then remove accordingly, either by scraping, sanding or power washing. Mildew must be removed with an appropriate solution.

APPLICATION

Coating can be applied by low pressure airless spray, roller or brush.

1 - 2 coats are required, depending on the porosity of the substrate. **ELCO Protekt-it PLUS** should be applied to a minimum of 60-100 microns.

Application Parameters

Do not apply below 10°C or above 85% relative humidity.

Ensure adequate air movement.

Cleaning

Wash up in hot water immediately after use.

COMMENTS

Use only **ELCO Remove-it** if cold water cleaning process is used in preference to hot water and follow instructions carefully.

Do not allow to rain on the object within 24 hours after application.

FIRST AID

* **If poisoning occurs**, contact a doctor or Poisons Information Centre.

* **If swallowed**, do not induce vomiting. Give a glass of water.

* **If skin contact occurs**, remove contaminated clothing and wash skin thoroughly with soap and water.

* **If overcome by fumes**, remove the person from contaminated area and apply artificial respiration if they are not breathing.

* **If in eyes**, hold eyes open, flood with water for at least 15 minutes and see a doctor.

TECHNICAL HELP LINE.

If you require any further information or have any questions please call us on toll free 1800 675 650 and one of our experienced staff will be more than happy to assist.

The statements above are compiled from our field of production and according to the latest technological developments and application techniques. Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet. ELCO International Pty Ltd and associated group of companies shall not be responsible for any damage or injury resulting from abnormal use of the material, from any failure to adhere or observe the recommendations, or from any hazards inherent in the nature of the material. It is the user's responsibility to evaluate the information contained herein and use this product safely and within the current laws and regulations.