

ELCO Shadow Remover

Commercial Grade Solvent Based Remover, formulated specifically for difficult removals and for removal of stubborn shadowing.

Can be readily used in conjunction with ELCO Remove-it

▪ **THE PRODUCT**

ELCO Shadow Remover is a solvent based cleaner for the removal of residual stains or shadows left behind from removal of spray enamels, acrylics and texter marker off unprotected masonry surfaces and surfaces protected with ELCO Tuff Coat or ELCO Protekt-it.

▪ **APPLICATION**

Apply to by brush and leave for 10 to 15 minutes. Apply more product as necessary to ensure the surface does not dry during this time. During application some agitation of the surface with a nylon brush may assist the removal process. On smooth and rough surfaces clean the surface with water and a brush or for optimum results, hot water pressure cleaning is recommended. On unpainted surfaces eg. brick and masonry, it may be necessary to repeat the application and pressure cleaning process until a satisfactory result is achieved.

▪ **SPECIFICATION SHEETS**

Before application refer to the corresponding Material Safety Data Sheets ELSRMSDS

Thinning: Do not thin

Wash Up: Water

▪ **SAFETY PRECAUTIONS**

- * **Keep out of reach of children.**
- * **Avoid contact with eyes,** wear safety goggles.
- * **Avoid contact with skin,** wear Impervious gloves, coveralls, boots and/or other resistant protective clothing.
- * **Avoid vapour (or) spray mist.** Ensure adequate ventilation.
- * **Do not smoke. Store in a safe, dry place** away from direct heat or any source of ignition.

* **Keep unwanted product in sealed containers** for disposal via special waste collection.

▪ **FIRST AID**

* **If poisoning occurs,** contact a doctor or Poisons Information Centre.

* **If swallowed,** do not induce vomiting. Give a glass of water.

* **If skin contact occurs,** remove contaminated clothing and wash skin thoroughly with soap and water.

* **If overcome by fumes** remove from contaminated area, apply artificial respiration if not breathing.

* **If in eyes,** hold eyes open, flood with water for at least 15 minutes and see a doctor.

TECHNICAL HELP LINE.

If you require any further information or have any questions please call us on tollfree 1800 675 650 and one of our experienced staff will be more than happy to assist.

The statements above are compiled from our field of production and according to the latest technological developments and application techniques. Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet. ELCO International Pty Ltd and associated group of companies shall not be responsible for any damage or injury resulting from abnormal use of the material, from any failure to adhere or observe the recommendations, or from any hazards inherent in the nature of the material. It is the users responsibility to evaluate the information contained herein and use this product safely and within the current laws and regulations.