



- ✓ Structural Cleaning
- ✓ Floor Coating
- ✓ Graffiti Protection
- ✓ Graffiti Removal
- ✓ Liquid Lamination
- ✓ ELCO Products

ABN 52 080 916 196

ELCO International Pty Ltd, 1 / 17 Stennett Road, INGLEBURN NSW 2565

Phone: (02) 9605 3000 (6 lines) * Fax: (02) 9605 3222 * Free Call: 1 800 675 650

email: elcointernational@ozemail.com.au

PRODUCT INFORMATION

Product Code: ELKL

KLEANIT

Product Description	<p>KLEANIT is a multi purpose super concentrated soluble alkaline detergent formulated for cleaning of practically any surface. The product in this container has the Department of Primary Industry's approval as a General Purpose Cleaning Aid, which means that it can also be used anywhere in the food industry.</p> <ul style="list-style-type: none"> * non flammable * will not harm sound paint work * safe on all hard surfaces * spray and wipe - one action cleaning <p>Formulated to break down mould, mildew, grease, oil, grime and food stains.</p>	
For use on	<p>Many interior and exterior solid surfaces e.g. raw masonry walls, driveways, pavements, painted surfaces, colorbond, timber, plastics, vinyl cladding, aluminium cladding, powder coated surfaces. Cleans just about anything e.g. oil, grease, dirt, dust, light carbon deposits, exhaust stains and more.</p>	
Product Information	<p>Colour</p> <p>Odour</p>	<p>Blue</p> <p>Low Odour</p>
Surface Preparation	<p>Physically remove any large deposits of undesirable material prior to application of KLEANIT</p>	
Application	<ul style="list-style-type: none"> * KLEANIT can be used in either hot or cold water, however hot water will speed up the cleaning process. * The most common concentration - 1:4 with water * can be diluted 1:40 with water * Apply by brush, swab or spray, leave for a short time then rinse off with a clean damp cloth. * For heavier soiling, use a stronger solution and leave to work for several minutes before rinsing or wiping off 	
Clean up	<p>Water</p>	
Notes / Limitations	<p>Ensure that the product is thoroughly mixed prior to application.</p>	
Do Not	<ul style="list-style-type: none"> * Allow to freeze or apply in freezing temperatures. 	

Issue date: 01.05.06
 Supersedes issue date: Second Issue
 Reason for issue: Update at time of factory move.

Approved by M.J. Collison
Protective Coatings Disclaimer

The technical information and suggestions for use and application presented herein are not intended to be exhaustive, but they represent the best information available to us and are believed to be reliable. They should not however be construed as controlling suggestions and there is no warranty or performance of our materials either expressed or implied. We urge that users of our materials conduct confirmatory tests to determine final stability for their specific end uses. Because this data sheet is subject to changes from time to time, it is the user's responsibility to check that this sheet is current prior to using this product.