



- ✓ Structural Cleaning
- ✓ Floor Coating
- ✓ Graffiti Protection
- ✓ Graffiti Removal
- ✓ Liquid Lamination
- ✓ ELCO Products

ABN 52 080 916 196

ELCO International Pty Ltd, 1 / 17 Stennett Road, INGLEBURN NSW 2565

Phone: (02) 9605 3000 (6 lines) * Fax: (02) 9605 3222 * Free Call: 1 800 675 650

email: elcointernational@ozemail.com.au

PRODUCT INFORMATION

Product Code: ELREN'SE

RESTORE N' SEALIT

Product Description	RESTORE N' SEALIT is a multi purpose water based clear barrier coating formulated to seal and protect a wide variety of surfaces. RESTORE N' SEALIT is water-resistant & will significantly reduce the absorption of water, oils & grease. RESTORE N' SEALIT prevents oxidation, rust, mould, mildew and UV damage. Stain resistant from salt water, acids, food spills, oils etc. Won't yellow, crack, peel or chip. Allows the substrate to breathe.	
For use on	Many interior and exterior solid surfaces e.g. raw masonry walls, driveways, pavements, painted surfaces, colorbond, timber, plastics, vinyl cladding, aluminium cladding, powder coated surfaces etc.	
Product Information	Gloss Level	Satin
	Abrasion Resistance	Good
	Exterior Durability	Excellent
	Odour	Low Odour
Surface Preparation	All surfaces should be thoroughly cleaned with ELCO International's multi purpose cleaner KLEANIT. Ensure that they are free of any grease, oil, silicon, dust or dirt. If the surface is or has been affected by mould then treat the surface appropriately prior to coating. Allow the surface to thoroughly dry.	
Application	<p>* Apply RESTORE N' SEALIT with soft, damp, lint free cloth, sponge, soft paint brush, roller or spray. Spread sufficient RESTORE N' SEALIT gently and consistently so that a clear film develops over the surface and that the surface has been evenly coated. Do not over work or rub surface excessively.</p> <p>* Under normal conditions of use, RESTORE N' SEALIT will be touch dry in 20 minutes or less and generally is recoatable after 1 hour.</p> <p>* A second coat is required for optimum protection on all surfaces. For extremely absorbent surfaces a third coat may be required.</p>	
Coverage	Depending on the nature of the surface, a spread rate of approximately 15 square metres per litre is achieved. This figure will be less on porous and rough surfaces.	
Clean up	Water	
Notes / Limitations	Ensure that the product is thoroughly mixed prior to application.	
Do Not	<p>* Thin RESTORE N' SEALIT</p> <p>* Allow the surface to be exposed to excessive water for a minimum 12 hours.</p> <p>* Allow to freeze or apply in freezing temperatures.</p>	

Issue date: 01.05.06
 Supersedes issue date: Second Issue
 Reason for issue: Update at time of factory move.

Approved by M.J. Collison

Protective Coatings Disclaimer

The technical information and suggestions for use and application presented herein are not intended to be exhaustive, but they represent the best information available to us and are believed to be reliable. They should not however be construed as controlling suggestions and there is no warranty or performance of our materials either expressed or implied. We urge that users of our materials conduct confirmatory tests to determine final stability for their specific end uses. Because this data sheet is subject to changes from time to time, it is the user's responsibility to check that this sheet is current prior to using this product.